

VCD SERIES

COLD STORAGE

Cold Storage used to store agricultural commodities such as **vegetables and fruits, fishery products and seafood, ice cubes or crystal ice, and other products** that require low temperature storage.

**VCD 90 - 9 TON****VCD 120 -12 TON****VCD 30 - 3 TON****VCD 60 -6 TON**

Cold Storage DAXTRO is customizable *(dimensions, capacity, temperature, and other specifications)* according to your needs.

- The cooling room panel is made of Polyurethane material (available thickness 100-150 mm)
- Customizable temperature ranging from -5°C to -25°C for various products
- Temperature that can be easily adjusted from outside the room with the Programmable Logic Controller (PLC) system
- Cold room with knock down panel structure (flexible, moveable, low shipping cost)
- Big Capacity Ready.



CUBE ICE MACHINE

CD SERIES



Daxtro Ice cube machines for various needs. Ice size, capacity, and other specifications can be adjusted to demand. Machines are available from 1 ton to 25 tons per day. If you are looking for an ice cube machine, Daxtro ready to provide the best offer for you.



CD 10
1 TON / DAY



CD 50
5 TON / DAY



CD 200
10 TON / DAY

CUBE ICE SPECIFICATION



Model		CD 10	CD 20	CD 30	CD 40	CD 50	CD 60	CD 80	CD 100	CD 200	CD 250
Specification	Capacity (ton/24hours)	1	2	3	4	5	6	8	10	20	25
	Refrigerant	R404A/R507, environmental friendly type									
	Compressor	Bitzer/Refcomp									
	Cooling Way	Water/Air	Water/Air	Water/Air	Water	Water	Water	Water	Water	Water	Water
	Qty of ice evaporator	4	8	12	16	18	24	30	36	36 (bigger)	42 (bigger)
	Compressor Power (HP)	4	9	14	23	28	34	44	2*28	4*28	3*44
	Reducer Motor (KW)	0,75	0,75	1,1	1,1	1,1	1,1	1,1*2	1,1*2	2,2*2	2,2*2
	Circulated Water Pump (KW)	0,25	0,37	0,37	0,75	0,75	0,75	1,1	0,75*2	0,75*4	0,75*5
Water Cooling	Water Cooling Pump (KW)	0,75	1,1	1,5	2,2	2,2	2,2	2,2	4	4	5,5
	Model of Tower	8T	15T	20T	25T	30T	40T	40T	50T	80T	100T
	Tower Motor (KW)	0,18	0,37	0,55	0,75	0,75	1,5	1,5	1,5	2,2	2,2
Air Cooling	Motor (KW)	0,38	0,72	1,7	/	2,4	/	3,2	/	/	/
	Fans Diameter (mm)	400*2	400*4	500*4	/	630*3	/	630*4	/	/	/
Dimension	length (mm)	1700/1800	1730/2150	2100/3158	2620	3110	3900	4980	5830	6250	6750
	width (mm)	1230/1650	1520/1640	1940/1950	1940	1940	1940	1980	1980	2310	2310
	height (mm)	1970/1750	2030/2030	2050/2030	2040	2040	2190	2300	2320	2470	2470
	Weight (Kg)	900	1200	1350	1550	1780	2100	3000	3900	5500	6500

TUBE ICE MACHINE

TD SERIES

Daxtro provides tube ice machines in various tonnages and capacities, ranging from 1 ton to 25 tons per day. The diameter and height of the ice can also be adjusted to your needs. The available ice sizes range from 2.8-10mm holes. Want to meet your ice consumption needs with a tube ice machine? Consult with our team and find the solution at Daxtro.



TD 300
30 TON/DAY



TD 100
10 TON/ DAY



TD 50
5 TON/DAY



TD 10
1 TON/DAY

TUBE ICE SPECIFICATION



Specification		Model										
		TD 10	TD 20	TD 30	TD 50	TD 50	TD 80	TD 100	TD 120	TD 150	TD 200	TD 300
Capacity		1	2	3	5	5	8	10	12	15	20	30
Refrigerant		R404A/R507, environmental friendly type										
Compressor		Blitzer/Refcomp										
Cooling Way		water/air	water/air	water/air	water	air	water	water	water	water	water	water
Compressor power (HP)		4	9	14	28	28	44	2*23	2*28	1*34 + 1*44	3*34	3*34 + 1*44
Culter motor (KW)		0,37	0,37	0,55	0,75	0,75	1,1	1,1	1,1	2,2	2,2	2,2
Reduction Ratio		01:15							0,1			
Circulated Water Pump (KW)		0,37	0,37	0,55	0,75	0,75	1,1	1,5	1,5	2,2	2,2	2*1,5
		40mm diameter: 1.65KW										
Water Cooling	Water Cooling Pump	0,75	1,1	1,5	2,2	/	2,2	4	4	4	5,5	7,5
	Tower Model	8T	15T	20T	30T	/	40T	50T	50T	60T	80T	125T
	Tower Motor Power	0,18	0,37	0,55	0,75	/	1,5	1,5	1,5	1,5	1,5	2,2
Air Cooling	Fans Diameter	400*2	400*4	500*4	/	630*3	/	/	/	/	/	/
	Motor Power (KW)	0,36	0,72	1,7	/	2,4	/	/	/	/	/	/
	length (mm)	1520/1600	1550/1650	1680/1930	1790	1750/3030	2200	2320/1450	2300/1600	2450/1500	2800/1600	3500/1700
Dimension	width (mm)	1000/1350	910/1090	950/1240	1080	1020/1130	1900	1820/1200	2130/1250	1820/1300	2130/1250	2300/1700
	height (mm)	2020/2010	2010/2300	2200/2260	2270	2250/1210	2400	1830/2600	2100/3200	1520/4100	2100/4800	2400/6150
Weight		900	1400	1750	2070	2400	3000	3200	3800	3925	6850	8500



FLAKE ICE MACHINE

FD SERIES

Daxtro Flake Ice Machine is in the form of small dry flakes, does not clump, and without water droplets. The shape of flake ice is blunt so it will not damage the stored material. It also suitable for use in the food industry, especially the fisheries and meat sectors. Cooling with flake ice is also more practical because the size of the ice is ideal and does not need to be crushed before use. So, ice can be used directly to cool the product.



FD 300
30 TON / DAY



FD 200
20 TON / DAY



FD 50
5 TON / DAY



FD 10
1 TON / DAY

PRODUCT



FLAKE ICE SPECIFICATION

Spesification	Model	FD10	FD20	FD50	FD80	FD100	FD150	FD200
Capacity		1	2	5	8	10	15	20
Refrigerant		R404A/R507, environmental friendly type						
Compressor brand		Bitzer/Refcomp						
Cooling Way		Air	Air	water	water	water	water	water
Compressor Power (HP)		6	9	44	23	34+44	34	
Reduer Motor (KW)		0.2	0.37	0.37	0.75	0.75	1.5	1.5
Circulated Water Pump (KW)		0.15	0.15	0.15	0.25	0.55	0.55	0.75
Dosing Pump (KW)		0.8	0.8	0.8	0.8	0.8	0.8	0.8
Water Cooling Pump(KW)				1.5	2.2	2.2	4	5.5
Air Cooling condenser (KW)		0.38	0.38	/	/	/	/	/
cooling tower motor (KW)				0.75	1.5	1.5	1.5	2.2
Dimension	length (mm)	1320	1760	2010	2100	2300	2900	3450
	width (mm)	1270	1110	1620	1940	1860	2200	2260
	height (mm)	1240	1300	1690	2050	2120	2380	2450
cooling tower				30T	40T	50T	60T	80T

APPLICATION



SLURRY ICE MACHINE

SD SERIES

Daxtro Slurry Ice Machine produces porridge-shaped ice with a small, soft texture. Slurry ice is suitable for cooling fish and meat to stay fresh because it can enter the inside of fish and meat products.

So, flexible machines with good ice quality. Production machine capacity is available from 1 ton to 20 tons per day.



PRODUCT & APPLICATIONS



SD 200
20 TON / DAY



SD 50
5 TON / DAY



SD 30
3 TON / DAY

SLURRY ICE SPECIFICATION

Specification		Model	SD10	SD20	SD30	SD50	SD50	SD100	SD100	SD200	SD200
Capacity (ton/day)			1	2	3	5	5	10	10	20	20
Refrigerant			R404A/R507, environmental friendly type								
Compressor brand			Copeland Scroll type			Copeland scroll/Bitzer/Refcomp		Bitzer/Refcomp			
Cooling Way			water	water	water	water	air	water	air	water	air
Power of scroll type (HP)			2HP	3HP	4HP	7.5HP	9HP	/	/	/	/
Power of piston type (HP)			1HP	2HP	4HP	9HP	9HP	14HP	18HP	28HP 6HE-28	34HP
Power reducer motor (KW)			0,55	0,75	0,75	1,5	1,5	1,5	1,5	1,5*2	1,5*2
sinking pump power (KW)			0,95	0,95	0,95	0,95	0,95	0,95	0,95	0,95*2	0,95*2
water pump power (KW)			0,55	0,55	0,55	0,75	/	1,1	/	1,5	/
Air	Diameter of fans		/	/	/	/	400*4	/	500*4	/	630*3
	Power of fans (KW)		/	/	/	/	180W*4	/	414W*4	/	550W*3
Dimension	length (mm)				1120		1710				3480
	width (mm)				1020		1430				2020
	height (mm)				1520		2170				1520



BLOCK ICE MACHINE

BD SERIES

Daxtro Block Ice Machine produces block-shaped ice (Non-Consumption) and can be used for industrial sectors, fishery products and meat products to maintain product quality and durability.

Daxtro block ice machines are available in a variety of production capacities, ranging from 500 kg to 50 tons per day. The size of the block ice also varies and can be adjusted according to demand.



BD 200
20 TON / DAY



BD 100
10 TON / DAY



BD 10
1 TON / DAY

PRODUCT



APPLICATION AGRICULTURAL



APPLICATION LIVE-STOCK



BLOCK ICE SPECIFICATION

Specification	Model	BD04	BD05	BD10	BD20	BD30	BD40	BD50	BD60	BD80	BD100	BD150	BD200	BD250	BD300
Capacity (Ton/24 hours)		0.4	0.5	1	2	3	4	5	6	8	10	15	20	25	30
Refrigerant		R404a/R507, environmental friendly type													
Power Form		220V/50Hz/1P		380V/50Hz/3P 220V/50Hz/1P		380V/50Hz/3P									
Compressor Brand		Copeland/Innotech		Copeland		Bitzer/Rafcomp									
Cooling Way		Air Cooling		Air Cooling/Water Cooling				Air Cooling/Water Cooling				Water Cooling/Evaporative Cooling			
Compressor Power (HP)		3HP	4HP	6HP/2*4HP	12HP	18HP	28HP	28HP	44HP	2*28HP	2*28HP	2*28+1*34HP	2*44+1*34 HP	2*44+2*34HP	4*44HP
Ice Harvest Way		Manual Lifting		Jack				Motor Powered							
Ice Block Motor Power (KW)		/		0.55KW	1.1KW	1.1KW	2.2KW	2.2KW	3KW	4KW	4KW	4KW	5.5KW	2*3KW	2*4KW
Water Cooling	Pump Power (KW)	/		0.75 KW	1.1 KW	1.5 KW	2.2KW	2.2KW	2.2KW	4KW	4KW	5.5KW	5.5KW	7.5KW	7.5KW
	Tower Model	/		8T	16T	25T	25T	36T	46T	56T	66T	86T	100T	125T	150T
	Motor Power (KW)	/		0.37	0.37	0.75	0.75	0.75	1.5	1.5	1.5	1.5	2.2	2.2	2.2
Air Cooling	Fan Diameter	400*2	400*2	400*2	400*4	500*4	500*6	600*4	630*4	630*4	630*6	/	/	/	/
	Motor Power (KW)	0.18*2	0.18*2	0.19*2	0.19*4	0.41*4	0.41*6	0.825*4	0.932*4	0.932*4	0.932*6	/	/	/	/
Machine Weight (Kg)		440kg	490kg	943kg	1291kg	1690kg	2920kg	2880kg	6000kg	7500kg	8450kg	10640kg	11977kg		18500kg



BAHASA INDONESIA

VCD SERIES

COLD STORAGE

Cold Storage digunakan untuk menyimpan komoditas pertanian seperti sayuran dan buah-buahan, produk perikanan dan hasil laut, es balok atau es kristal, serta produk lain yang memerlukan penyimpanan pada suhu rendah.

**VCD 90 - 9 TON****VCD 120 -12 TON****VCD 30 - 3 TON****VCD 60 -6 TON**

Cold Storage DAXTRO dapat disesuaikan

(dari dimensi, kapasitas, suhu, hingga spesifikasi lainnya) sesuai kebutuhan Anda.

- Panel ruang pendingin menggunakan material Polyurethane (tersedia ketebalan 100–150 mm).
- Suhu dapat disesuaikan dari -5°C hingga -25°C untuk berbagai jenis produk.
- Pengaturan suhu mudah dilakukan dari luar ruangan dengan sistem Programmable Logic Controller (PLC).
- Ruang pendingin menggunakan struktur panel knock down (fleksibel, mudah dipindahkan, biaya pengiriman lebih rendah).

Siap untuk kapasitas besar.



CUBE ICE MACHINE

CD SERIES



Mesin es batu Daxtro untuk berbagai kebutuhan. Ukuran, kapasitas, dan spesifikasi es lainnya dapat disesuaikan dengan permintaan. Mesin tersedia dari 1 ton hingga 25 ton per hari. Jika Anda mencari mesin es batu, Daxtro siap memberikan penawaran terbaik untuk Anda.



CD 10
1 TON / HARI



CD 50
5 TON / HARI



CD 200
10 TON / HARI

CUBE ICE SPESIFIKASI



Model		CD 10	CD 20	CD 30	CD 40	CD 50	CD 60	CD 80	CD 100	CD 200	CD 250
Specification	Capacity (ton/24hours)	1	2	3	4	5	6	8	10	20	25
	Refrigerant	R404A/R507, environmental friendly type									
	Compressor	Bitzer/Refcomp									
	Cooling Way	Water/Air	Water/Air	Water/Air	Water	Water	Water	Water	Water	Water	Water
	Qty of ice evaporator	4	8	12	16	18	24	30	36	36 (bigger)	42 (bigger)
	Compressor Power (HP)	4	9	14	23	28	34	44	2*28	4*28	3*44
	Reducer Motor (KW)	0,75	0,75	1,1	1,1	1,1	1,1	1,1*2	1,1*2	2,2*2	2,2*2
	Circulated Water Pump (KW)	0,25	0,37	0,37	0,75	0,75	0,75	1,1	0,75*2	0,75*4	0,75*5
Water Cooling	Water Cooling Pump (KW)	0,75	1,1	1,5	2,2	2,2	2,2	2,2	4	4	5,5
	Model of Tower	8T	15T	20T	25T	30T	40T	40T	50T	80T	100T
	Tower Motor (KW)	0,18	0,37	0,55	0,75	0,75	1,5	1,5	1,5	2,2	2,2
Air Cooling	Motor (KW)	0,38	0,72	1,7	/	2,4	/	3,2	/	/	/
	Fans Diameter (mm)	400*2	400*4	500*4	/	630*3	/	630*4	/	/	/
Dimension	length (mm)	1700/1800	1730/2150	2100/3158	2620	3110	3900	4980	5830	6250	6750
	width (mm)	1230/1650	1520/1640	1940/1950	1940	1940	1940	1980	1980	2310	2310
	height (mm)	1970/1750	2030/2030	2050/2030	2040	2040	2190	2300	2320	2470	2470
	Weight (Kg)	900	1200	1350	1550	1780	2100	3000	3900	5500	6500

TUBE ICE MACHINE

TD SERIES

Daxtro menyediakan mesin es tabung dalam berbagai ton dan kapasitas, mulai dari 1 ton hingga 25 ton per hari. Diameter dan tinggi es juga dapat disesuaikan dengan kebutuhan Anda. Ukuran es yang tersedia berkisar dari lubang 2,8-10 mm. Ingin memenuhi kebutuhan konsumsi es Anda dengan mesin es tabung? Konsultasikan dengan tim kami dan temukan solusinya di Daxtro.



TD 300
30 TON/HARI



TD 100
10 TON/HARI



TD 50
5 TON/HARI



TD 10
1 TON/HARI

TUBE ICE SPESIFIKASI



Specification	Model	TD 10	TD 20	TD 30	TD 50	TD 80	TD 100	TD 120	TD 150	TD 200	TD 300
Capacity		1	2	3	5	5	8	10	12	15	30
Refrigerant		R404A/R507, environmental friendly type									
Compressor		Bitzer/Refcomp									
Cooling Way		water/air	water/air	water/air	water	air	water	water	water	water	water
Compressor power (HP)		4	9	14	28	28	44	2*23	2*28	1*34 + 1*44	3*34
Cutlar motor (KW)		0,37	0,37	0,55	0,75	0,75	1,1	1,1	1,1	2,2	2,2
Reduction Ratio		01:15						0,1			
Circulated Water Pump (KW)		0,37	0,37	0,55	0,75	0,75	1,1	1,5	1,5	2,2	2,2
								40mm diameter: 1.65KW			
Water Cooling	Water Cooling Pump	0,75	1,1	1,5	2,2	/	2,2	4	4	4	5,5
	Tower Model	8T	15T	20T	30T	/	40T	50T	50T	60T	80T
Air Cooling	Tower Motor Power	0,18	0,37	0,55	0,75	/	1,5	1,5	1,5	1,5	2,2
	Fans Diameters	400*2	400*4	500*4	/	630*3	/	/	/	/	/
Dimension	Motor Power (KW)	0,36	0,72	1,7	/	2,4	/	/	/	/	/
	length (mm)	1520/1600	1550/1650	1680/1930	1790	1750/2030	2200	2320/1450	2300/1600	2450/1500	2800/1600
Weight	width (mm)	1000/1350	910/1090	950/1240	1080	1020/1130	1900	1820/1200	2130/1250	1820/1300	2130/1250
	height (mm)	2020/2010	2010/2300	2200/2260	2270	2250/1210	2400	1830/2600	2100/3200	1520/4100	2100/4800

FLAKE ICE MACHINE

FD SERIES

Mesin Es Flake Daxtro menghasilkan es berbentuk serpihan kecil yang kering, tidak menggumpal, dan bebas dari tetesan air. Dengan bentuk yang tumpul, es serpih ini aman digunakan karena tidak merusak material yang disimpan. Mesin ini sangat ideal untuk industri makanan, khususnya sektor perikanan dan daging. Pendinginan menggunakan es serpih juga lebih efisien, karena ukuran es yang optimal sehingga tidak memerlukan proses penghancuran sebelum digunakan. Es dapat langsung diaplikasikan untuk menjaga kesegaran produk.



FD 300
30 TON / HARI



FD 200
20 TON / HARI



FD 50
5 TON / HARI



FD 10
1 TON / HARI

PRODUCT



APPLICATION



FLAKE ICE SPESIFIKASI

Spesification	Model	FD10	FD20	FD50	FD80	FD100	FD150	FD200
Capacity		1	2	5	8	10	15	20
Refrigerant		R404A/R507, environmental friendly type						
Compressor brand		Bitzer/Refcomp						
Cooling Way		Air	Air	water	water	water	water	water
Compressor Power (HP)		6	9	44	23	34+44	34	
Reduer Motor (KW)		0.2	0.37	0.37	0.75	0.75	1.5	1.5
Circulated Water Pump (KW)		0.15	0.15	0.15	0.25	0.55	0.55	0.75
Dosing Pump (KW)		0.8	0.8	0.8	0.8	0.8	0.8	0.8
Water Cooling Pump(KW)				1.5	2.2	2.2	4	5.5
Air Cooling condenser (KW)		0.38	0.38	/	/	/	/	/
cooling tower motor (KW)				0.75	1.5	1.5	1.5	2.2
Dimension	length (mm)	1320	1760	2010	2100	2300	2900	3450
	width (mm)	1270	1110	1620	1940	1860	2200	2260
	height (mm)	1240	1300	1690	2050	2120	2380	2450
cooling tower				30T	40T	50T	60T	80T



SLURRY ICE MACHINE

SD SERIES

Mesin Es Slurry Daxtro menghasilkan es berbentuk bubuk dengan tekstur yang kecil dan lembut. Es slurry sangat cocok untuk mendinginkan ikan dan daging agar tetap segar karena dapat masuk ke dalam bagian produk ikan dan daging.

Mesin ini fleksibel dengan kualitas es yang baik. Kapasitas produksi mesin tersedia mulai dari 1 ton hingga 20 ton per hari.



PRODUCT & APPLICATIONS



SD 200
20 TON / HARI



SD 50
5 TON / HARI



SD 30
3 TON / HARI

SLURRY ICE SPESIFIKASI

Specification		Model	SD10	SD20	SD30	SD50	SD50	SD100	SD100	SD200	SD200
Capacity (ton/day)			1	2	3	5	5	10	10	20	20
Refrigerant			R404A/R507, environmental friendly type								
Compressor brand			Copeland Scroll type			Copeland scroll/Bitzer/Refcomp		Bitzer/Refcomp			
Cooling Way			water	water	water	water	air	water	air	water	air
Power of scroll type (HP)			2HP	3HP	4HP	7.5HP	9HP	/	/	/	/
Power of piston type (HP)			1HP	2HP	4HP	9HP	9HP	14HP	18HP	28HP 6HE-28	34HP
Power reducer motor (KW)			0,55	0,75	0,75	1,5	1,5	1,5	1,5	1,5*2	1,5*2
sinking pump power (KW)			0,95	0,95	0,95	0,95	0,95	0,95	0,95	0,95*2	0,95*2
water pump power (KW)			0,55	0,55	0,55	0,75	/	1,1	/	1,5	/
Air	Diameter of fans		/	/	/	/	400*4	/	500*4	/	630*3
	Power of fans (KW)		/	/	/	/	180W*4	/	414W*4	/	550W*3
Dimension	length (mm)				1120		1710				3480
	width (mm)				1020		1430				2020
	height (mm)				1520		2170				1520



BLOCK ICE MACHINE

BD SERIES

Mesin Es Balok Daxtro menghasilkan es berbentuk balok (Non-Konsumsi) yang dapat digunakan untuk sektor industri, produk perikanan, dan produk daging guna menjaga kualitas dan ketahanan produk.

Mesin es balok Daxtro tersedia dalam berbagai kapasitas produksi, mulai dari 500 kg hingga 50 ton per hari. Ukuran es balok juga bervariasi dan dapat disesuaikan sesuai permintaan.



BD 200
20 TON / HARI



BD 100
10 TON / HARI



BD 10
1 TON / HARI

PRODUCT



APPLICATION AGRICULTURAL



APPLICATION LIVE-STOCK



BLOCK ICE SPESIFIKASI

Specification	Model	BD04	BD05	BD10	BD20	BD30	BD40	BD50	BD60	BD80	BD100	BD150	BD200	BD250	BD300
Capacity (Ton/24 hours)		0.4	0.5	1	2	3	4	5	6	8	10	15	20	25	30
Refrigerant		R404a/R507, environmental friendly type													
Power Form		220V/50Hz/1P		380V/50Hz/3P 220V/50Hz/1P		380V/50Hz/3P									
Compressor Brand		Copeland/Imvotach		Copeland		Bitzer/Rafcomp									
Cooling Way		Air Cooling		Air Cooling/Water Cooling				Air Cooling/Water Cooling				Water Cooling/Evaporative Cooling			
Compressor Power (HP)		3HP	4HP	6HP/2*4HP	12HP	18HP	28HP	28HP	44HP	2*28HP	2*28HP	2*28+1*34HP	2*44+1*34 HP	2*44+2*34HP	4*44HP
Ice Harvest Way		Manual Lifting		Jack				Motor Powered							
Ice Bad Motor Power (KW)		/		0.55KW	1.1KW	1.1KW	2.2KW	2.2KW	3KW	4KW	4KW	4KW	5.5KW	2*3KW	2*4KW
Water Cooling	Pump Power (KW)	/		0.75 KW	1.1 KW	1.5 KW	2.2KW	2.2KW	2.2KW	4KW	4KW	5.5KW	5.5KW	7.5KW	7.5KW
	Tower Model	/		8T	15T	25T	25T	30T	40T	50T	60T	80T	100T	125T	150T
	Motor Power (KW)	/		0.37	0.37	0.75	0.75	0.75	1.5	1.5	1.5	1.5	2.2	2.2	2.2
Air Cooling	Fan Diameter	400*2	400*2	400*2	400*4	500*4	500*6	600*4	630*4	630*4	630*6	/	/	/	/
	Motor Power (KW)	0.18*2	0.18*2	0.19*2	0.19*4	0.41*4	0.41*6	0.825*4	0.932*4	0.932*4	0.932*6	/	/	/	/
Machine Weight (Kg)		440kg	490kg	943kg	1291kg	1690kg	2920kg	2880kg	6000kg	7500kg	8450kg	10640kg	11977kg		18500kg

